

EAGLE 53 PILOTHOUSE MOTORYACHT

EQUIPMENT LIST

Built to CE Specs

Jan 2014

One (1) Unit Eagle 53 Pilothouse F.O.B. Ningbo or Shanghai, China

- Hull = Solid laminate using Vinylester resin in external layers and fitted with internal FRP grid.
- House & deck = FRP laminate w/ structural coring as required; 2 coats white bilge paint; non-skid decks.
- 3 coats of Int'l Paint's 2 part epoxy on bare hull below waterline stripe. 2 coats Micron Extra anti-fouling paint.
- Propulsion engines = Twin Cummins QSB6.7-250 HP electronic diesel engines w/ ZF 80A gears at 2.50:1 ratio, 12 V electric shift; 12 V x 160 amp alternators.
- Racor fuel filters and U.S. Coast Guard approved flexible fuel hose.
- 8 kw Diesel Genset with sound shield; 120 AH starting battery and accessories.
- Molded FRP airfoil rudders with stainless steel stocks and cores.
- Prop shafts of #17 Aquatech stainless, PYI dripless shaft seals, and 4 bladed bronze props.
- Two station hydraulic steering.
- Two station Cummins, electronic engine/transmission controls.
- 2 Fuel tanks of molded fire retardant FRP with gelcoated baffled interior, total 830 U.S. gallons.
- 2 Water tanks of molded FRP with gelcoated baffled interior; total 250 U.S. gallons.
- Hart Tank Tenders – to monitor levels in 2 fuel tanks and 1 water tank in addition to tank sight gauges.
- Foam/lead sandwich eng room insulation; reinforced aluminum foil outer layer covered w/ perforated aluminum sheet.
- Springfield Marine adjustable height, pilot seats w/ padded, movable armrests; footrests; black vinyl in PH; white on FB.
- Aluminum cabin sole beams. Teak & holly cabin soles (veneered). Interior teak varnished with low gloss, matte finish.
- Galvanized, hot dipped, fabricated steel, engine bed saddles installed on molded longitudinal beams.
- 2 Electric toilets; 2 x 25 gal. toilet holding tanks, each w/ macerator & both with deck pump-out & gravity drains.
- Pressurized water system with 20 U.S. gallons water heater.
- Two electric bilge pumps with automatic float switches & 1 manual bilge pump.
- Two Automatic 12 volt shower sump pumps.
- Watertight engine room bulkheads.
- International navigation lights & electric air horn.
- Three (3) 12 volt pantograph windshield wipers.
- Stainless steel shore power inlet = 50 Amp rating with Galvanic isolator 50amp; stainless steel phone and TV inlet.
- Blue Sea main circuit breaker panel with volt & ammeters for 12V D.C. and 120V A.C.
- Batteries = 4 each heavy duty, 12 Volt, 200 amp hours with selector switch.
- 40 amp battery charger and battery isolators.
- Flybridge wind breaker made of a st. st. frame with lightly tinted acrylic panels on top of bridge coaming.
- 10 Lewmar, aluminum, opening screened ports in staterooms and washrooms.
- 5 Aluminum frame, sliding windows in saloon; 7 fixed aluminum frame fixed windows in pilothouse.
- 2 Aluminum doors w/ windows in pilothouse and 1 sliding st. st., windowed door on aft salon bulkhead.
- Port and starboard bulwark doors outboard of pilothouse doors.
- Salon & pilothouse seats, vinyl covered; berth mattresses, fabric covered.
- Norcold or equal AC/DC 2 doors refrigerator, including separate freezer compartment.
- Electric cook top range, 3 burners & microwave oven.
- Folding, painted aluminum radar mast w/ radar base & spreader lights.
- Type 316 stainless steel deck hardware as listed:
- Bow pulpit and double rails of 1-1/4" dia. tube; boat deck double rails of 1-1/4" dia. tube.
- Swim platform of st/st. & teak; st/st. swim ladder installed on swim platform.
- Cockpit access ladder to upper deck with hatch overhead.
- Bow mooring bitt; mooring chocks at bow, midships & stern; single bow anchor roller assembly.
- Emergency tiller access plate and emergency tiller; flagpole socket (with teak flagpole).
- Steel shipping cradle & shipping cover.



Transpacific Marine Co., Ltd.

**7F.-2, No.176, Sec. 1, Zhongxiao E. Rd.,
Zhongzheng Dist., Taipei City 100, Taiwan**

TEL: 886-2-2351-2225 FAX: 886-2-2394-1138

Email: transpac@ms2.hinet.net

Website: www.transpacificmarine.com